



Technical Data GW09K-DT GW10K-DT GW12K-DT GW15K-DT GW17K-DT GW20K-DT GW25K-DT

| DC Input Data | GW09K-DT | GW10K-DT | GW12K-DT | GW15K-DT | GW17K-DT | GW20K-DT | GW25K-DT |
|---------------------------|------------------------|----------|----------|------------------|------------------|------------------|------------------|
| Max. allowed PV Power [W] | 11700 | 13000 | 15600 | 19500 | 22100 | 26000 | 32500 |
| Nominal DC Power [W] | 9200 | 10200 | 12300 | 15400 | 17500 | 20500 | 25800 |
| Max. DC voltage [V] | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 | 1000 |
| MPPT voltage range [V] | 260~850 | 260~850 | 260~850 | 260~850 | 260~850 | 260~850 | 260~850 |
| Starting voltage [V] | 250 | 250 | 250 | 250 | 250 | 250 | 250 |
| Max. DC current [A] | 22/11 | 22/11 | 22/11 | 22/22 | 22/22 | 22/22 | 27/27 |
| No. of DC connectors | 3 | 3 | 3 | 4 | 4 | 4 | 6 |
| No. of MPPTs | 2 | 2 | 2 | 2 (can parallel) | 2 (can parallel) | 2 (can parallel) | 2 (can parallel) |
| DC connector | MC4/ Phoenix/ Amphenol | | | | | | |

| AC Output Data | GW09K-DT | GW10K-DT | GW12K-DT | GW15K-DT | GW17K-DT | GW20K-DT | GW25K-DT |
|---------------------|-----------------------------|----------|----------|----------|----------|----------|----------|
| Normal AC power [W] | 9000 | 10000 | 12000 | 15000 | 17000 | 20000 | 25000 |
| Max. AC power [W] | 9000 | 10000 | 12000 | 15000 | 17000 | 20000 | 25000 |
| Max. AC current [A] | 15 | 17 | 19 | 25 | 25 | 30 | 37 |
| Normal AC output | 50/60Hz; 400Vac | | | | | | |
| AC output range | 45~55Hz/55~65Hz; 310~480Vac | | | | | | |
| THDi | <1.5% | | | | | | |
| Power factor | 0.8 leading~0.8 lagging | | | | | | |
| Grid connection | 3W/N/PE | | | | | | |

| Efficiency | GW09K-DT | GW10K-DT | GW12K-DT | GW15K-DT | GW17K-DT | GW20K-DT | GW25K-DT |
|----------------------------|----------|----------|----------|----------|----------|----------|----------|
| Max. efficiency | 98.0% | 98.0% | 98.0% | 98.2% | 98.2% | 98.4% | 98.4% |
| Euro efficiency | >97.7% | >97.7% | >97.7% | >97.7% | >97.7% | >98.1% | >98.1% |
| MPPT adaptation efficiency | 99.9% | 99.9% | 99.9% | 99.9% | 99.9% | 99.9% | 99.9% |

| Protection | GW09K-DT | GW10K-DT | GW12K-DT | GW15K-DT | GW17K-DT | GW20K-DT | GW25K-DT |
|----------------------------------|-----------------------|----------|----------|----------|----------|----------|----------|
| Residual current monitoring unit | Integrated | | | | | | |
| Anti-islanding protection | Integrated | | | | | | |
| DC switch | Integrated (optional) | | | | | | |
| AC over current protection | Integrated | | | | | | |
| Insulation monitoring | Integrated | | | | | | |

| Certifications & Standards | GW09K-DT | GW10K-DT | GW12K-DT | GW15K-DT | GW17K-DT | GW20K-DT | GW25K-DT | |
|----------------------------|--|--|--|--|---|---|---|---|
| Grid regulation | VDE0126-1-1, G83/2, ERDF-NOI-RES_13E | VDE-AR-N 4105, AS4777.2/3, VDE0126-1-1, MEA&PEA, G59/3, NRS097-2-1, IEC61727, EN50438 ERDF-NOI-RES_13E | VDE-AR-N4105, AS4777.2/3, IEC61727, VDE0126-1-1, EN50438, NRS097-2-1, G59/3, ERDF-NOI-RES_13E; | VDE-AR-N 4105, AS4777.2/3, VDE0126-1-1, MEA&PEA, G59/3, NRS097-2-1, IEC61727, EN50438 ERDF-NOI-RES_13E | VDE-AR-N 4105, IEC61727, VDE0126-1-1, EN50438, G59/3; | VDE-AR-N 4105, IEC61727, VDE0126-1-1, EN50438, G59/3; | VDE-AR-N 4105, IEC61727, VDE0126-1-1, EN50438, G59/3; | VDE-AR-N 4105, IEC61727, VDE0126-1-1, EN50438, G59/3; |
| Safety | IEC62109-1&-2, AS3100 | | | | | | IEC62109-1&-2 | |
| EMC | EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12 | | | | | | | |

| General Data | GW09K-DT | GW10K-DT | GW12K-DT | GW15K-DT | GW17K-DT | GW20K-DT | GW25K-DT |
|-----------------------------|---------------------------|----------|----------|----------|----------|----------|----------|
| Dimensions (WxHxD) [mm] | 516*650*203 | | | | | | |
| Weight [kg] | 39 | | | | | | 40 |
| Mounting | Wall bracket | | | | | | |
| Ambient temperature range | -25~60°C (>45°C derating) | | | | | | |
| Relative humidity | 0~95% | | | | | | |
| Max. operating altitude | 4000m(> 3000m derating) | | | | | | |
| Protection degree | IP65 | | | | | | |
| Topology | Transformerless | | | | | | |
| Night power consumption [W] | <1 | | | | | | |
| Cooling | Fan cooling | | | | | | |
| Noise emission [dB] | <45 | | | | | | |
| Display | 5.0" LCD | | | | | | |
| Communication | USB2.0; RS485 or WiFi | | | | | | |
| Standard warranty [years] | 5/10/15/20/25 (optional) | | | | | | |

DT Series (Dual-MPPT, Three-Phase)

GoodWe DT series inverter adopts cutting-edge technology in photovoltaic fields. Higher conversion efficiency and lower energy losses are guaranteed to maximize customer satisfaction. With its reliable power grid support management and high protective class, the DT series is compatible with different types of branded solar panels and is also ideal for commercial rooftop systems. This safe and reliable series is the first choice for residential, commercial installations and power plants.

- Maximum Efficiency up to 98.5%
- European Efficiency up to 98.1%
- MPPT Efficiency up to 99.9%
- DC switch
- IP65 dust-proof and water-proof rating
- 45°C full-load output
- Super large 5-inch LCD
- 30% lighter than similar products
- Multiple monitoring and communication
- up to 80 pieces can be integrated in one system